



P204 VERSATILE MATERIAL SOLUTION

P204 multi-end roving represents a versatile solution for a wide range of SMC (Sheet Molding Compound) applications, especially where reduced glass changeovers are needed when manufacturing multiple types of parts.

- P204 multi-end roving is made from Advantex® continuous glass filaments.
- Compatible with polyester, vinyl-ester and polyurethane resin systems.

Product Benefits

Efficient processability

- Due to its outstanding impregnation and wet-out characteristics the product enables around 30% glass loading and thus reduced glass changeovers when making multiple parts with different end use requirement.

Excellent part surface finish

- The product is designed for use with Low Shrink (LS) and Low Profile (LP) formulations enabling enhanced 'Class-A' surface aesthetics.
- The product allows for pigmentable applications as well.

Excellent performance

- The product is a multi-functional solution in that its proprietary sizing helps the final part with excellent mechanical properties.

Enhanced Service Life

- Advantex® glass helps fight corrosion, enhancing service life compared to standard E-glass.

Application

P204 product is designed to provide optimal performance in Sheet Molding Compound (SMC) transportation applications such as automotive 'Class-A' or structural parts. Also, it can be used for the manufacture of general purpose end-use products.



Availability

P204 is available worldwide.

MANUFACTURING REGION	PRODUCT/DOFF DESCRIPTION	EXTERNAL Ø MM (IN)	HEIGHT MM (IN)	NET WEIGHT KG (LB)
Europe	P204 2400/4800 Tex	290	260	19
North America	P204 2400/4800 Tex	285(11.2)/ 350(13.7)	265(10.4)	19.9(43.8)/31(68.3)
Asia Pacific	P204 2400/4800 Tex	280	265	18
Asia Pacific	P204 2400/4800 Tex	290	260	19

Technical Characteristics (Nominal Values)

LINEAR WEIGHT OF ROVING (TEX)	YIELDS (YDS/LB)	LOSS ON IGNITION (%) ISO 1887:1995
2400	207	1.20
4800	103	1.20

Packaging and Labeling

Each bobbin is protected by a plastic film (Tack-Pak™). Please do not remove film during use. Creel-Pak™ packaging is available upon request.

Each bobbin has a self-adhesive identification label, showing the product reference and the production date. Each pallet has at least one identification label detailing the product reference, pallet net and gross weights, production date and pallet production code. The packaging system is designed to allow short term stacking of two pallets. When stacking two high, care should be taken to correctly and smoothly place the top pallet. It is recommended to use a plywood plate between the two pallets in order not to damage the lower pallet.

MANUFACTURING REGION	PRODUCT /DOFF DESCRIPTION	DOFF Ø (MM/IN)	PALLET DIM LxWxH CM (IN)	LAYERS PER PALLET	DOFFS PER LAYER	NUMBER OF ENDS	PALLET NET WEIGHT KG (LB)
Europe	P204 2400/4800 Tex	290	90 x 120 x 122 & 120 x 120 x 122	4	16/12	1 to 16	1000/1220
North America	P204 2400/4800 Tex	285 (11.2)	114 x 114 x 122 & 142 x 109 x 122 (44.9 x 44.9 x 48 & 55.9 x 42.9 x 48)	3/4	16/12	16/12	955/1488 (2,105/3,280)
Asia Pacific	P204 2400/4800 Tex	280	115 x 115 x 95	3	16	1 to 16	864
Asia Pacific	P204 2400/4800 Tex	290	113 x 113 x 120	3	16	2	800

Storage

Unless otherwise specified, it is recommended to store glass fiber products in a cool, dry area. Ideal conditions are at a temperature between 10°C and 35°C and a relative humidity between 35% and 85%. The glass fiber products must remain in their original packaging material until the point of usage. If the storage temperature is below 15°C, it is recommended that the product be stored in the workshop, within its original packaging, at least 24 hours prior to use to help prevent condensation. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water. When stored properly, the product can be used up to 2 years from the date of manufacture, and retesting is advised after 1 year from the initial production date to insure optimum performance.



Americas

Owens Corning Composite Materials, LLC.

One Owens Corning Parkway
Toledo, Ohio, USA 43659
1-800-GET-PINK®

Europe

European Owens Corning Fiberglas Sprl.

166 Chaussée de la Hulpe
B-1170 Brussels
Belgium
+32 3 674 8211

Asia Pacific

Owens Corning Shanghai Regional Headquarters

40/F, Pudong Kerry Parkside,
115 Fang Dian Road, Pudong,
Shanghai, 201204, China
+86-21-6101 9666

<https://www.owenscorning.com/composites> | Composites@owenscorning.com

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law, safety code or insurance regulation. We reserve the right to modify this document without prior notice.

Image copyright: shutterstock.com, image for application illustration only.

Pub number: 10010187-B. P204_MER_product data sheet_ww_10-2018_Rev9. January 2019. English.

THE PINK PANTHER™ & © 1964–2019 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. © 2019 Owens Corning. All Rights Reserved.