



OPTISPRAY® F ROVING

REDUCE RESIN, INCREASE PERFORMANCE

OptiSpray® F Roving represents a compelling solution for fabricators that want to save time and resin while increasing the performance of their products.

- Multi-end gun roving reinforcement using Advantex® glass fiber, which combines the electrical and mechanical properties of traditional E-glass with the acid corrosion resistance of E-CR glass.
- Advantex® glass roving has a sizing system designed to provide optimal performance for spray-up applications where fast wet-out speed is preferred.

FOR FAST WET-OUT AND EASY WORKABILITY

Product Benefits

Increased Efficiency

- Low fuzz combined with easy chopping, roll-out and uniform dispersion saves time.

Reduced Cost

- Higher glass loading with optimal resin consumption reduces the amount of expensive resin required.

Great Performance

- Good mechanical properties, great surface quality, excellent conform-ability, doesn't trap air, low spring back.

Fast Wet-out

- Designed to provide optimal performance for spray-up applications where fast wet-out speed is preferred; great performance in various types of part complexities.

Packaging to Reduce Waste and Increase Floorspace

- The new, optional 4-high pallet design increases the amount of fiberglass material in the standard pallet footprint by 33% enabling producers to fit more pounds within a distribution center, on a truck during delivery, and in the manufacturing site with no impact to floor space.

Applications

OptiSpray® F Roving can be used in a variety of spray-up applications including: boats, truck caps, vehicle body parts, bath tubs, showers, spas, tanks, and applications with complex molds or sharp curvatures.

Technical Characteristics
(Nominal Values)

LINEAR WEIGHT OF ROVING (Tex)	YIELDS (Yds/Lb)	LOSS ON IGNITION (%) ISO 1887: 1995
2400	207	1.25
3000	165	1.25

Availability and Packaging
(Standard Reference)

- Each OptiSpray® F doff is protected by a tack-wrap polythene film and identified by an individual label; please do not remove film during use.
- Creel-Pak™ and customer specific packaging may be available upon request.

PRODUCT	DOFF Ø (MM)	PALLET DIMENSIONS L X W (CM)	LAYERS PER PALLET	DOFFS PER LAYER	TOTAL NUMBER OF DOFFS	CREEL-PAK™	PALLETS APPROX. FIBERGLASS
						NUMBER OF ENDS	WEIGHT* (KG)
OptiSpray® F Rov. Creel-Pak™ 4E 2400/3000	303	129.5 x 96.5	3	16	48	4	941
OptiSpray® F Rov. Creel-Pak™ 2E 2400/3000	303	129.5 x 96.5	3	16	48	2	941
OptiSpray® F Rov. Close Top™ 2400/3000	303	129.5 x 96.5	3	16	48	Individual Boxes	1104
Optional OptiSpray® F Rov. Creel-Pak™ 2E 2400	303	129.5 x 96.5	4	16	64	2	1255

*Add 35 to 45 kg to obtain gross weight.

Labeling

Each doff has a self-adhesive identification label, showing the product reference and the production date.

Each pallet has five identification labels detailing the product reference, pallet net and gross weights, production date and pallet production code.

Storage

OptiSpray® F Roving should be stored in its original packaging in a dry and cool place. Best conditions are at temperatures from 10° to 35°C (50 to 95°F) and humidity between 35%-85%. If you store the product at lower temperatures, please move the soon-to-be-processed pallets to the production area 24 hours ahead of time. You can stack pallets, one-on-one with a plywood plank between the two.



Americas

Owens Corning Composite Materials, LLC.

One Owens Corning Parkway
Toledo, Ohio, USA 43659
1-800-GET-PINK™

Europe

European Owens Corning Fiberglas Sprl.

166 Chaussée de la Hulpe
B-1170 Brussels
Belgium
+32 3 674 8211

Asia Pacific

Owens Corning Shanghai Regional Headquarters

40/F, Pudong Kerry Parkside,
115 Fang Dian Road, Pudong,
Shanghai, 201204, China
+86-21-6101 9666

<https://www.owenscorning.com/composites> | Composites@owenscorning.com

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law, safety code or insurance regulation. We reserve the right to modify this document without prior notice.