



EU - DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulations (EU) No. 305/2011 Construction Product Regulation

1. Name and contact address of the manufacturer as required pursuant to Article 11(5):

**European Owens Corning Fiberglas SPRL
Chaussée de la Hulpe,166
1170 Watermael-Boitsfort, Belgium**

2. Registered trade name or registered trade mark

ARcoteX® 5326

3. Unique identification code of the product and type:

ARcoteX® 5326 600 tex AR Glass Fiber Roving

4. Batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Material Number and Manufacturing date: Refer to Pallet Label

5. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

The AR glass fibers are intended to be used in concrete, mortar and other cementitious mixes for construction and for the manufacturing of construction products

6. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

7. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

And under the supervision of Notified Body

Not applicable

8. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Not applicable

9. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

UBAtc issued ETA 17/0169 on the base of EAD 260002-00-0301



EU - DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulations (EU) No. 305/2011 Construction Product Regulation

10. Declared performances

Essential characteristics	Performance	Standard
Size content	0,80 % by mass	ISO 1887
Average filament diameter	19 μm	ISO 1888
Linear density	600 tex (g/1000m)	ISO 1889
Tensile strength of strands	> 1000 MPa > 700 MPa	ISO 3341 EN14649
Alkali resistance (SIC Strength)	≥ 250 MPa	EN14649
Effect on Consistency of Concrete	NA	
Effect on Strength of concrete	NA	

11. The performance of the product identified in point 3 is in conformity with the declared performances in point 10.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 1.

Signed for and on behalf of the manufacturer by:

G rard Tardy

Cem-FIL[®] Product Engineer

OCV CHAMBERY INTERNATIONAL

767 Quai des Allobroges - BP 929

73009 Chamb ry Cedex - FRANCE

Chamb ry, 2019, January 24th

OCV CHAMBERY INTERNATIONAL
S.A.S. au capital de 235.000.060  
Si ge Social : 767, quai des Allobroges
73000 CHAMBERY
324 420 785 R.C.S. Chamb ry