



CEM-FIL[®]

DRY MIX & MORTARS

THE EASY WAY TO FIND THE CEM-FIL[®]/ANTI-CRAK[®] SOLUTION

APPLICATION - MARKET SEGMENT		CEM-FIL [®] 70 3, 6, 9, 12mm	ANTI-CRAK [®] HD 3, 6, 9, 12, 18mm	CEM-FIL [®] 60 6, 12, 18mm	CEM-FIL [®] 62 6, 12mm	ANTI-CRAK [®] HP 12, 24mm
Dry Mix	Renders/Stucco	●	●	●	●	●
	Repair Mortars		●	●	●	●
	Finishing Mortars	●			●	●
	Top Screed Mortars			●	●	●

- Primary product
- Product for special needs

PERFORMANCE BENEFITS GUIDE

RECOMMENDED DOSAGE RANGE (BY % WT)	0.02 - 0.5%		1 - 3%		
	CEM-FIL [®] 70 3, 6, 9, 12mm	ANTI-CRAK [®] HD 3, 6, 9, 12, 18mm	CEM-FIL [®] 60 6, 12, 18mm	CEM-FIL [®] 62 6, 12, 18mm	ANTI-CRAK [®] HP 12, 24mm
Dispersion	●	●	●	●	●
Workability	●	●	●	●	●
Impact Resistance			●	●	●
Finishing	●	●	●	●	●
Prevention of Plastic Shrinkage Cracking	●	●	●	●	●
Prevention of Temperature & Shrinkage Cracking			●	●	●
Flexural Strength			●	●	●

- Excellent
- Very Good
- Good



HOW WE BUILD NOW