



FIBERGLAS® BATT & ROLLS FOR COMMERCIAL & RESIDENTIAL APPLICATIONS



Pink Fiberglas™ Thermal Batt Insulation (No Facing)

For wood- and metal-framed wall, floor, and ceiling assemblies. Can be used in contact with CMU or poured concrete. Can be left exposed. Vapor retarder can be added to assembly when required.


| | |
|------------------------------------|-------------------------------|
| Flame Spread Index ² | <25 |
| Smoke Developed Index ² | <50 |
| Construction Type | ALL |
| Specification | ASTM C665 ³ Type I |



Pink Fiberglas™ Thermal Batt Insulation (Kraft Faced)

For wood- and metal-framed wall¹, floor, and ceiling assemblies. Can be used in contact with CMU or poured concrete. Kraft facing is a Class II vapor retarder. Cannot be left exposed – must be covered by a 15-minute thermal barrier.

| | |
|------------------------------------|---|
| Water Vapor Permeance | 1 |
| Flame Spread Index ² | N/R |
| Smoke Developed Index ² | N/R |
| Construction Type | III, IV, V |
| Specification | ASTM C665 ³ Type II, Class C, Cat. 1 |



Pink Fiberglas™ Flame Spread 25 (FSK Faced)

For wood- and metal-framed wall, floor, and ceiling assemblies. Can be used in contact with CMU or poured concrete. FSK facing is a Class II vapor retarder. Can be left exposed. Not recommended for below-grade walls.

| | |
|------------------------------------|--|
| Water Vapor Permeance | .5 |
| Flame Spread Index ² | <25 |
| Smoke Developed Index ² | <50 |
| Construction Type | ALL |
| Specification | ASTM C665 FSK Type III, Class A, Cat. 1 ASTM C665 ³ PSK Type II, Class A, Cat. 1 |



Sound Attenuation Batts (No Facing)

For wood- and metal-framed wall or ceiling assemblies. Unfaced and can be left exposed. Labeled for use in thermal envelope as needed.

| | |
|------------------------------------|-------------------------------|
| Flame Spread Index ² | <25 |
| Smoke Developed Index ² | <50 |
| Construction Type | ALL |
| Specification | ASTM C665 ³ Type I |

¹ Tabbed (flanged) facing may be installed via friction-fit, face stapling, or inset stapling.
² "Tabless" (FastBatt) facing is designed for friction-fit installation only.
³ ASTM E84: Flame spread/smoke developed <25/50.
 ASTM C665: Blankets for light frame and mfd housing.

| CONSTRUCTION APPLICATION | R-VALUE | FRAMING TYPE | WIDTH | LENGTH | THICKNESS | TYPE | FACING |
|-----------------------------|---------|--------------|--------------------|----------------|-----------|------|------------------|
| Exterior Walls (2x4) | | | | | | | |
| | 11 | Wood | 15", 23" | 93" | 3.5" | Batt | Kraft |
| | 13 | Wood | 15" | 93", 105" | 3.5" | Batt | Unfaced/Kraft |
| | 13 | Wood | 15" | 384" | 3.5" | Roll | Kraft |
| | 13 | Wood | 15.25" | 93", 105" | 3.5" | Batt | Kraft (FastBatt) |
| | 13 | Wood | 23" | 93" | 3.5" | Batt | Unfaced/Kraft |
| | 13 | Wood | 19.25" | 93" | 3.5" | Batt | Unfaced |
| | 15 | Wood | 15" | 93", 105" | 3.5" | Batt | Unfaced/Kraft |
| | 15 | Wood | 23" | 93" | 3.5" | Batt | Unfaced/Kraft |
| | 13 | Metal | 16", 24" | 96" | 3.5" | Batt | Unfaced/FSK |
| | 13 | Metal | 16" | 96" | 3.5" | Batt | Kraft |
| | 15 | Metal | 16", 24" | 96" | 3.5" | Batt | Unfaced |
| | 15 | Metal | 16" | 96" | 3.5" | Batt | Kraft |
| Exterior Walls (2x6) | | | | | | | |
| | 19 | Wood | 15", 23" | 48", 93", 105" | 6.5" | Batt | Unfaced |
| | 19 | Wood | 15", 23" | 48", 93", 105" | 6.5" | Batt | Kraft |
| | 19 | Wood | 15", 23" | 470" | 6.25" | Roll | Kraft |
| | 19 | Wood | 15.25" | 93", 105" | 6.5" | Batt | Kraft (FastBatt) |
| | 19 | Wood | 19.25" | 48" | 6.5" | Batt | Unfaced/Kraft |
| | 20 | Wood | 15" | 93", 105" | 5.5" | Batt | Unfaced |
| | 20 | Wood | 15" | 93", 105" | 5.5" | Batt | Kraft |
| | 20 | Wood | 23" | 93" | 5.5" | Batt | Kraft |
| | 21 | Wood | 15" | 93" | 3.5" | Batt | Kraft (FastBatt) |
| | 21 | Wood | 15", 23" | 93", 105" | 5.5" | Batt | Unfaced |
| | 21 | Wood | 15", 23" | 93", 105" | 5.5" | Batt | Kraft |
| | 19 | Wood, Metal | 15", 16", 23", 24" | 93", 96" | 6.5" | Batt | FSK |
| | 21 | Wood, Metal | 15", 16" | 93", 96" | 5.5" | Batt | FSK |
| | 19 | Metal | 16", 24" | 96" | 6.5" | Batt | Unfaced |
| | 19 | Metal | 16", 24" | 96" | 3.5" | Batt | Kraft |
| | 21 | Metal | 16", 24" | 96" | 5.5" | Batt | Unfaced |
| | 21 | Metal | 16" | 96" | 5.5" | Batt | Kraft |

| CONSTRUCTION APPLICATION | R-VALUE | FRAMING TYPE | WIDTH | LENGTH | THICKNESS | TYPE | FACING |
|---------------------------|---------|--------------|------------------|-----------|-----------|------|----------------------------------|
| Interior Walls | | | | | | | |
| Sound Attenuation Batts | 8 | Metal | 16", 24" | 96" | 2.5" | Batt | Unfaced |
| Sound Attenuation Batts | 11 | Wood | 15.25" | 93", 105" | 3.5" | Batt | Unfaced |
| Sound Attenuation Batts | 11 | Wood | 23.25" | 93" | 3.5" | Batt | Unfaced |
| Sound Attenuation Batts | 11 | Metal | 16", 24" | 96" | 3.5" | Batt | Unfaced |
| Sound Attenuation Batts | 19 | Metal | 16", 24" | 96" | 6.5" | Batt | Unfaced |
| Basement Walls | | | | | | | |
| Basement Blanket | 11 | | 48" | 600" | 3.5" | Roll | PSK Perf'd/ Unfaced & Perf'd. |
| Basement Blanket | 19 | | 48" | 360" | 5.5" | Roll | PSK Perf'd/ Unfaced & Perf'd. |
| Ceilings | | | | | | | |
| SonoBatts | 19 | | 24" | 48" | 6.5" | Batt | Unfaced |
| | 22 | Metal | 24" | 48" | 6.75" | Batt | Unfaced |
| | 25 | Metal | 16", 24" | 96" | 8" | Batt | Unfaced |
| Cathedral Ceilings | | | | | | | |
| | 22 | Wood | 23" | 48" | 6.75" | Batt | Unfaced |
| | 30C | Wood | 15.5", 23.75" | 48" | 8.25" | Batt | Unfaced |
| | 30C | Wood | 15.5", 23.75" | 48" | 8.25" | Batt | Kraft |
| | 38C | Wood | 15.5", 23.75" | 48" | 10.25" | Batt | Unfaced |
| | 38C | Wood | 15.5", 23.75" | 48" | 10.25" | Batt | Kraft |
| Attics | | | | | | | |
| | 19 | Wood | 15" | 48", 105" | 6.5" | Batt | Unfaced |
| | 19 | Wood | 15", 23" | 470" | 6.25" | Roll | Unfaced |
| | 19 | Wood | 15", 23" | 470" | 6.25" | Roll | Kraft |
| | 22 | Wood | 23" | 48" | 6.75" | Batt | Unfaced |
| | 22 | Wood | 23" | 48" | 6.75" | Batt | Kraft |
| | 25 | Wood | 16", 24" | 96" | 8" | Batt | Unfaced |
| | 25 | Wood | 16", 24" | 96" | 8" | Batt | Kraft |
| | 30 | Wood | 16", 19.25", 24" | 48" | 10" | Batt | Kraft |
| | 30 | Wood | 15", 23" | 300" | 9" | Roll | Unfaced |
| | 30 | Wood | 16", 19.25", 24" | 48" | 10" | Batt | Unfaced |
| | 38 | Wood | 16", 19.25", 24" | 48" | 12.5" | Batt | Unfaced |
| | 38 | Wood | 16", 24" | 48" | 12.5" | Batt | Kraft |

| CONSTRUCTION APPLICATION | R-VALUE | FRAMING TYPE | WIDTH | LENGTH | THICKNESS | TYPE | FACING |
|--------------------------|---------|--------------|------------------|-----------|-----------|------|---------|
| Floors | | | | | | | |
| | 13 | Wood | 19.25" | 93" | 3.5" | Batt | Unfaced |
| | 13 | Metal | 16", 24" | 96" | 3.5" | Batt | FSK |
| | 19 | Wood | 15" | 48", 93" | 6.5" | Batt | Kraft |
| | 19 | Wood | 15" | 48", 105" | 6.5" | Batt | Unfaced |
| | 19 | Wood | 15", 23" | 470" | 6.25" | Roll | Unfaced |
| | 19 | Wood | 15", 23" | 470" | 6.25" | Roll | Kraft |
| | 19 | Wood | 19.25" | 48" | 6.5" | Batt | Unfaced |
| | 19 | Wood | 19.25" | 48" | 6.5" | Batt | Kraft |
| | 19 | Wood | 16", 24" | 93", 96" | 6.5" | Batt | FSK |
| | 25 | Wood | 16", 24" | 96" | 8" | Batt | Kraft |
| | 25 | Wood | 16", 24" | 96" | 8" | Batt | Unfaced |
| | 30 | Wood | 15", 23" | 300" | 9" | Roll | Unfaced |
| | 30 | Wood | 16", 19.25", 24" | 48" | 10" | Batt | Unfaced |
| | 30 | Wood | 16", 19.25", 24" | 48" | 10" | Batt | Kraft |
| | 38 | Wood | 16", 19.25", 24" | 48" | 12" | Batt | Unfaced |
| | 38 | Wood | 16", 19.25", 24" | 48" | 12" | Batt | Kraft |
| | 19 | Wood, Metal | 16", 24" | 93", 96" | 6.5" | Batt | FSK |
| | 21 | Wood, Metal | 15" | 93" | 5.5" | Batt | FSK |
| | 21 | Wood, Metal | 16" | 96" | 6" | Batt | FSK |
| | 22 | Metal | 24" | 48" | 6.75" | Batt | Unfaced |
| | 25 | Metal | 16", 24" | 96" | 8" | Batt | Unfaced |
| | 25 | Metal | 16", 24" | 96" | 8" | Batt | Kraft |
| | 30 | Metal | 16", 24" | 48" | 10" | Batt | FSK |
| | 38 | Metal | 16", 24" | 48" | 12" | Batt | FSK |

OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659

1-800-GET-PINK® | www.owenscorning.com