



FIBERGLAS™ Batts and Rolls

Facings for Residential and Commercial Insulation



UNFACED INSULATION

For wood and metal framed wall, floor and ceiling assemblies. Can be used in contact with CMU or poured concrete. Can be left exposed. Vapor retarder can be added to assembly when required.

Facer Appearance	No Facing
Insulation Type	Fiberglass
Product Name	EcoTouch® Thermal Batt Insulation
Water Vapor Permeance	>5%
Flame Spread Index†	<25
Smoke Developed Index†	<50
Construction Type	III, IV, V
Specification	ASTM C 665*
	Type I



KRAFT FACED INSULATION

For wood and metal framed wall, floor and ceiling assemblies. Can be used in contact with CMU or poured concrete. Kraft facing is a Class II vapor retarder. Cannot be left exposed - must be covered by a 15 minute thermal barrier.

*Tabbed (flanged) facing may be installed via friction fit, face stapling or inset stapling. "Tabless" (FastBatt) facing is designed for friction fit installation only.


Facer Appearance	Brown
Insulation Type	Fiberglass Batt
Product Name	EcoTouch® Thermal Batt Insulation
Water Vapor Permeance	1
Flame Spread Index†	N/R#
Smoke Developed Index†	N/R#
Construction Type	III, IV, V
Specification	ASTM C 665*
	Type II, Class C, Category 1



FOIL FACED INSULATION

For wood and metal framed wall, floor and ceiling assemblies. Can be used in contact with CMU or poured concrete. Foil facing is a Class II vapor retarder. Cannot be left exposed - must be covered by a 15 minute thermal barrier. Not recommended for below grade walls.

Facer Appearance	Foil
Insulation Type	Fiberglass Batt
Product Name	Thermal Batt Insulation
Water Vapor Permeance	.5
Flame Spread Index†	75
Smoke Developed Index†	150
Construction Type	III, IV, V
Specification	ASTM C 665*
	Type III, Class C, Category 1



PSK/FSK FACED INSULATION

For wood and metal framed wall, floor and ceiling assemblies. Can be used in contact with CMU or poured concrete. PSK/FSK facing is a Class II vapor retarder. Can be left exposed. Not recommended for below grade walls.

Facer Appearance	FSK - Foil PSK - White
Insulation Type	Fiberglass Batt
Product Name	EcoTouch® Flame Spread 25
Water Vapor Permeance	.5
Flame Spread Index†	<25
Smoke Developed Index†	<50
Construction Type	All
Specification	ASTM C 665 FSK
	Type III, Class A, Category 1
	ASTM C 665* PSK
	Type II, Class A, Category 1



QUIETZONE® ACOUSTIC BATTS

For wood framed interior wall or ceiling assemblies only. Facing is not a vapor retarder and cannot be left exposed - must be covered by 15 minute thermal barrier. Not intended or rated to be used for thermal envelope.

Facer Appearance	No Facing and Kraft Faced
Insulation Type	Fiberglass
Product Name	QuietZone® Acoustic Batts
Water Vapor Permeance	>5%
Flame Spread Index†	N/R#
Smoke Developed Index†	N/R#
Construction Type	III, IV, V
Specification	ASTM C 665*
	Type II, Class C, Category 2



SOUND ATTENUATION BATTS (SAB'S)

For metal framed wall or ceiling assemblies. Unfaced, can be left exposed. Labeled for use in thermal envelope as needed.

Facer Appearance	No Facing
Insulation Type	Fiberglass Batt
Product Name	Sound Attenuation Batts
Water Vapor Permeance	>5%
Flame Spread Index†	<25
Smoke Developed Index†	<50
Construction Type	All
Specification	ASTM C 665*
	Type 1

*ASTM C 665: Blankets for light frame and mfd housing.

†ASTM E 84: Flame spread/smoke developed <25/50.


Construction Application	R-Value	Framing Type	Width	Length	Thickness	Type	Facing
Exterior Walls (2x4)							
	11	Wood	15"	93", 105"	3.5"	Batt	Unfaced/ Kraft
	11	Wood	15"	94"	3.5"	Rolled Batt	Unfaced
	11	Wood	15", 23"	94"	3.5"	Rolled Batt	Kraft
	11	Wood	16"	96"	3.5"	Batt	Unfaced
	11	Wood	23"	93"	3.5"	Batt	Unfaced/ Kraft
	13	Wood	15"	93", 105"	3.5"	Batt	Unfaced/ Kraft
FastBatt	13	Wood	15.25"	93", 105"	3.5"	Batt	Kraft
	13	Wood	15"	94"	3.5"	Rolled Batt	Unfaced/ Kraft
	13	Wood	15", 23"	384"	3.5"	Roll	Kraft
	13	Wood	23"	93"	3.5"	Batt	Unfaced/ Kraft
	13	Wood	19.25"	93"	3.5"	Batt	Unfaced
	13	Wood	23"	93"	3.5"	Batt	Unfaced/ Kraft
	15	Wood	15", 23"	93", 105"	3.5"	Batt	Unfaced/ Kraft
	15	Wood	23"	93"	3.5"	Batt	Unfaced/ Kraft
	11	Metal	16", 24"	96"	3.5"	Batt	Unfaced/ Kraft
	13	Metal	16", 24"	96"	3.5"	Batt	Unfaced/ Foil/FSK
	13	Metal	16"	96"	3.5"	Batt	Kraft
	15	Metal	16", 24"	96"	3.5"	Batt	Unfaced
	15	Metal	16"	96"	3.5"	Batt	Kraft/Foil
Exterior Walls (2x6)							
	19	Wood	15", 23"	48", 93", 105"	6.25"	Batt	Unfaced
	19	Wood	15", 23"	48", 93", 105"	6.25"	Batt	Kraft
	19	Wood	15"	94"	6.25"	Rolled Batt	Unfaced
	19	Wood	15", 23"	94"	6.25"	Rolled Batt	Kraft
	19	Wood	15", 23"	470"	6.25"	Roll	Kraft
FastBatt	19	Wood	15.25"	93", 105"	6.25"	Batt	Kraft
	20	Wood	15", 23"	93", 105"	5.5"	Batt	Unfaced
	20	Wood	15", 23"	93", 105"	5.5"	Batt	Kraft
	21	Wood	15", 23"	93", 105"	5.5"	Batt	Unfaced
	21	Wood	15", 23"	93", 105"	5.5"	Batt	Kraft
	21	Wood	15"	93", 105"	5.5"	Batt	Kraft
	19	Wood, Metal	15", 16", 23", 24"	93", 96"	6.25"	Batt	FSK
	21	Wood, Metal	15", 16"	93", 96"	5.5"	Batt	FSK
	19	Metal	16", 24"	96"	6.25"	Batt	Unfaced
	19	Metal	16", 24"	96"	3.5"	Batt	Kraft
	19	Metal	16", 24"	96"	6.25"	Batt	Foil
	21	Metal	16", 24"	96"	5.5"	Batt	Unfaced
	21	Metal	16"	96"	5.5"	Batt	Kraft

Construction Application	R-Value	Framing Type	Width	Length	Thickness	Type	Facing
Interior Walls							
QuietZone® Insulation	NA	Wood	15.25", 23.25"	93", 105"	3.5"	Batt	Unfaced
QuietZone® Insulation	NA	Wood	15", 23"	93"	3.5"	Batt	Kraft
QuietZone® Insulation	NA	Metal	16"	93"	5.5"	Batt	Unfaced
Sound Attenuation Batts	NA	Metal	16", 24"	96"	2.5"	Batt	Unfaced
Sound Attenuation Batts	NA	Metal	16", 24"	96"	3.5"	Batt	Unfaced
Basement Walls							
	19	Wood	48"	470"	6.25"	Roll	Unfaced
	11		48"	600"	3.5"	Roll	Unfaced
	19		24"	48"	5.5"	Roll	PSK Perf'd.
Ceilings							
	22	Metal	24"	48"	6.75"	Batt	Unfaced
	25	Metal	16", 24"	96"	8"	Batt	Unfaced
Sonobatts® Insulation	11	NA	24"	48"	3.5, 6.25"	Batt	Unfaced
Sonobatts® Insulation	11	NA	24"	48"	3.5", 6.25"	Batt	Kraft
Sonobatts® Insulation	19	NA	24"	48"	3.5, 6.25"	Batt	Unfaced
Sonobatts® Insulation	19	NA	24"	48"	3.5", 6.25"	Batt	Kraft
Cathedral Ceilings							
	22	Wood	15", 23"	48"	6.75"	Batt	Unfaced
	22	Wood	15", 23"	48"	6.75"	Batt	Kraft
	30C	Wood	15.5", 23.75"	48"	8.25"	Batt	Unfaced
	30C	Wood	15.5", 23.75"	48"	8.25"	Batt	Kraft
	38C	Wood	15.5", 23.75"	48"	10.25"	Batt	Unfaced
	38C	Wood	15.5", 23.75"	48"	10.25"	Batt	Kraft
Attics							
	19	Wood	15"	48", 105"	6.25"	Batt	Unfaced
	19	Wood	15"	48"	6.25"	Batt	Kraft
	19	Wood	15", 23"	470"	6.25"	Roll	Unfaced
	19	Wood	15", 23"	470"	6.25"	Roll	Kraft
	19	Wood	30"	470"	6.25"	Roll	Kraft
	22	Wood	15", 23"	48"	6.75"	Batt	Unfaced
	22	Wood	15", 23"	48"	6.75"	Batt	Kraft
	25	Wood	23"	96"	8"	Batt	Unfaced
	25	Wood	16", 24"	96"	8"	Batt	Kraft
	30	Wood	12", 16", 24"	48"	9.5"	Batt	Kraft
	30	Wood	15", 23"	300"	9"	Roll	Unfaced
	30	Wood	16", 19.25", 24"	48"	9.5"	Batt	Unfaced
	30	Wood	23"	48.5"	9.5"	Batt	Unfaced
	38	Wood	16", 24"	48"	12"	Batt	Unfaced
	38	Wood	16", 24"	48"	12"	Batt	Kraft
	49	Wood	16", 24"	48"	14"	Batt	Unfaced
	49	Wood	16", 24"	48"	14"	Batt	Kraft
	30	Metal	16", 24"	48"	9.5"	Batt	Foil

Construction Application	R-Value	Framing Type	Width	Length	Thickness	Type	Facing
Floors							
	13	Wood	11", 19.25"	93"	3.5"	Batt	Unfaced
	13	Wood	11"	93"	3.5"	Batt	Kraft
	13	Wood	23"	96"	3.5"	Batt	FSK E
	15	Wood	11"	105"	3.5"	Batt	Unfaced
	19	Wood	11"	93"	6.25"	Batt	Unfaced
	19	Wood	11", 15"	48", 93"	6.25"	Batt	Kraft
	19	Wood	15"	48", 105"	6.25"	Batt	Unfaced
	19	Wood	15", 23"	470"	6.25"	Roll	Unfaced
	19	Wood	15", 23"	470"	6.25"	Roll	Kraft
	19	Wood	19.25"	48"	6.25"	Batt	Unfaced
	19	Wood	19.25"	48"	6.25"	Batt	Kraft
	19	Wood	23"	93", 96"	6.25"	Batt	FSK E
	19	Wood	23"	93", 96"	6.25"	Batt	PSK E
	25	Wood	16", 24"	96"	8"	Batt	Kraft
	25	Wood	23"	96"	8"	Batt	Unfaced
	25	Wood	23"	96"	8"	Batt	FSK E
	30	Wood	15", 23"	300"	9"	Roll	Unfaced
	30	Wood	16", 19.25", 24"	48"	9.5"	Batt	Unfaced
	30	Wood	19.25"	48"	9.5"	Batt	Kraft
	30	Wood	23"	48.5"	9.5"	Batt	Unfaced
	38	Wood	19.25"	48"	12"	Batt	Unfaced
	38	Wood	19.25"	48"	12"	Batt	Kraft
	19	Wood, Metal	15", 16", 23", 24"	93", 96"	6.25"	Batt	FSK
	21	Wood, Metal	15", 16"	93", 96"	5.5"	Batt	FSK
	22	Metal	24"	48"	6.75"	Batt	Unfaced
	25	Metal	16", 24"	96"	8"	Batt	Unfaced
	25	Metal	16"	96"	8"	Batt	FSK
	30	Metal	16", 24"	48"	9.5"	Batt	FSK
	30	Metal	24"	48"	9.5"	Batt	FSK E
	30	Metal	24"	48"	9.5"	Batt	PSK E
	38	Metal	16", 24"	48"	12"	Batt	FSK
	38	Metal	24"	48"	12"	Batt	FSK E



OWENS CORNING INSULATING SYSTEMS, LLC
 ONE OWENS CORNING PARKWAY
 TOLEDO, OHIO, USA 43659
1-800-GET-PINK®
www.owenscorning.com



Pub. No. 10021569-B. Printed in U.S.A. June 2018.
 THE PINK PANTHER™ & © 1964–2018 Metro-Goldwyn-Mayer Studios Inc.
 All Rights Reserved. The color PINK is a registered trademark of Owens Corning.
 © 2018 Owens Corning. All Rights Reserved.