



Self-Supporting Through Wall Flashing

Drip Edge

Fastener with Thermally Isolated Washer by Cladding Attachment System Manufacturer

NFFPA 285 Compliant Air & Water Barrier

Thermafiber® RainBarrier® CI Plus High Compressive Mineral Wool Insulation

Cladding Attachment System Recommended by Panel Manufacturer

NFFPA 285 Compliant Panel- Maximum Weight per Cladding Attachment System Manufacturer

Screw with Air & Water Sealing Washer (Optional)

NFFPA 285 Compliant Air & Water Barrier- Wrap into Rough Opening and Tie into Window or Door Assembly Per Manufacturer's Instructions to Create Continuous Air & Water Barrier

Owens Corning® Thermafiber® UltraBatt™ Mineral Wool Insulation (Optional)

5/8" Type X Exterior Gypsum Sheathing

Min. 3/2" 18 Ga. Galvanized Steel Studs at 24" O.C. Max.

5/8" Type X Gypsum Board

Owens Corning
Enclosure Solutions
 Steel Stud Wall System

Opening Sill Detail

Date: 9-20-19

Dwg. no. ES-SS-204

Vertical Section

NOTE: This drawing is a general reference intended to show common wall system assembly. Actual details for each product will vary, therefore, details for each project must be reviewed and approved by the Architect of Record. Refer to Manufacturers' Product Literature for product data and installation instructions. Manufacturers assume no responsibility for final project drawings or field installation.