



NATURAL-THERM® PRO

Closed Cell Spray Foam

PROVEN NEXT-GEN PERFORMANCE



Our new Natural-Therm® Pro spray foam insulation delivers greater flexibility with testing for more applications and the ability to spray at lower temperature settings.

KEY FEATURES

- Built on the consistent, applicator friendly, low-VOC¹ backbone of Natural-Therm® 2.0 HFO.
- Optimized for improved reactivity in the spring/fall transition seasons
- Tested for new commercial credentials, making it the go-to choice for specifiers and sprayers alike.
- Backed by an industry-leading team of field technicians and building science experts that are ready to support your most complex residential and commercial projects.

	NATURAL-THERM® 2.0 HFO	NATURAL-THERM® PRO
Key Feature		
R-Value (@ 1 inch)	> 7	> 7
Yield (board feet per set)	4,500–5,000+	4,500–5,000+
UL GreenGuard Gold	Certified	Certified
Fire Assemblies for Interior and Exterior Walls	Limited Assemblies	Extensive Assemblies
C1029 <i>Commercial Standard</i>	—	✓
Air & Water Barrier <i>Assemblies for Exterior Walls</i>	—	✓
Air Barrier Association of America (ABAA) Certified	—	✓
Proportioner Settings	—	Ability to spray at lower temps

¹www.ul.com/gg